

TRIFÁSICO

MODELO		UM CST 36 3F	UM CST 42 3F	UM CST 48 3F	UM CST 60 3F
Código		3NGR2100	3NGR2105	3NGR2110	3NGR2115
Referencia UI		GUD100T/A-T	GUD125T/A-T	GUD140T/A-T	GUD160T/A-T
Referencia UE		GUD100W/NhA-X	GUD125W/NhA-X	GUD140W/NhA-X	GUD160W/NhA-X
Potencia	Frio (W)	10000 (3200 - 11500)	12100 (3600 - 12500)	13400 (3600 - 13500)	14500 (3600 - 14500)
	Calor (W)	12000 (2900 - 14500)	13500 (3900 - 15500)	15500 (3900 - 15500)	17000 (3900 - 17000)
Potencia -10°C	(W)	8060	9070	10410	11420
Eficiencia energética	SEER	6.1	6.1	5.6	6.1
	SCOP	4	4	3.8	4
Clase energética	Frio / Calor	A++ / A+	A+ / A	A+ / A	A++ / A
Consumo eléctrico	Frio (W)	3000	4050	4700	5200
	Calor (W)	3400	4150	4500	4800
Corriente	Frio (A)	5	5.9	7.2	7.6
	Calor (A)	5.3	6.1	6.2	7.2
Alimentación	(V / f / Hz)	380 - 415 / 3 / 50	380 - 415 / 3 / 50	380 - 415 / 3 / 50	380 - 415 / 3 / 50
Rango de temperatura interior	Frio (°C)	+16 - +30	+16 - +30	+16 - +30	+16 - +30
	Calor (°C)	+16 - +30	+16 - +30	+16 - +30	+16 - +30
Rango de temperatura exterior	Frio (°C)	-20 - +48	-20 - +48	-20 - +48	-20 - +48
	Calor (°C)	-20 - +24	-20 - +24	-20 - +24	-20 - +24
Conexiones	Líquido (Pul.)	3/8	3/8	3/8	3/8
	Gas (Pul.)	5/8	5/8	5/8	5/8
Longitud precargada	(m)	5	5	7.5	7.5
Longitud máxima total (UI/UE)	(m)	75	75	75	75
Longitud vertical máxima	(m)	30	30	30	30
Cable de comunicación	(m)	2 × 0.75	2 × 0.75	2 × 0.75	2 × 0.75
Panel Ancho / alto / fondo	(mm)	950 / 52 / 950	950 / 52 / 950	950 / 52 / 950	950 / 52 / 950
Embalaje panel Ancho / alto / fondo	(mm)	1033 / 112 / 1038	1033 / 112 / 1038	1033 / 112 / 1038	1033 / 112 / 1038
Panel Peso neto / bruto	(kg)	6 / 9.5	6 / 9.5	6 / 9.5	6 / 9.5
UNIDAD INTERIOR					
Cable de alimentación	(n° × s)	3 × 1.5	3 × 1.5	3 × 1.5	3 × 1.5
Caudal de aire	(m ³ /h)	1500	1800	1900	2000
Presión sonora	(dB(A))	42 - 48	42 - 49	45 - 51	48 - 52
Potencia sonora	(dB(A))	59	60	61	61
Unidad Ancho / alto / fondo	(mm)	840 / 240 / 840	840 / 290 / 840	840 / 290 / 840	840 / 290 / 840
Embalaje Ancho / alto / fondo	(mm)	963 / 325 / 963	963 / 379 / 963	963 / 379 / 963	963 / 379 / 963
Unidad Peso neto / bruto	(kg)	31 / 38	33 / 41	36 / 44	36 / 44
UNIDAD EXTERIOR					
Cable de alimentación	(n° × s)	3 × 6	5 × 2.5	5 × 2.5	5 × 2.5
Caudal de aire	(m ³ /h)	5900	5900	5900	6600
Presión sonora	(dB(A))	55	56	57	57
Potencia sonora	(dB(A))	70	71	72	72
Refrigerante		R32	R32	R32	R32
Carga de refrigerante	(kg)	2.5	2.65	2.8	3.6
Carga adicional	(g/m)	40	40	40	40
Unidad Ancho / alto / fondo	(mm)	940 / 820 / 460	940 / 820 / 460	940 / 820 / 460	900 / 1345 / 340
Embalaje Ancho / alto / fondo	(mm)	1073 / 868 / 563	1073 / 868 / 563	1073 / 868 / 563	1033 / 1395 / 443
Unidad Peso neto / bruto	(kg)	89 / 101	95 / 107	99 / 111	112 / 122

Descarga la aplicación **Gree+** escaneando este código QR:

