

TRIFÁSICO

MODELO		UM CDT 36 3F	UM CDT 42 3F	UM CDT 48 3F	UM CDT 60 3F
Código		3NGR1160	3NGR1165	3NGR1170	3NGR1175
Referencia UI		GUDI00PS/A-T	GUDI25PS/A-T	GUDI40PS/A-T	GUDI60PS/A-T
Referencia UE		GUDI00W/NhA-X	GUDI25W/NhA-X	GUDI40W/NhA-X	GUDI60W/NhA-X
Potencia	Frio (W)	10000 (3200 - 11500)	12100 (3600 - 12500)	13400 (6000 - 14500)	16000 (7400 - 16500)
	Calor (W)	12000 (2900 - 14500)	13500 (3900 - 15500)	15500 (5200 - 17000)	17000 (6200 - 18500)
Potencia -10°C	(W)	8060	9070	10410	11420
Eficiencia energética	SEER	6.1	5.6	5.6	5.6
	SCOP	4	4	3.8	3.8
Clase energética	Frio / Calor	A++ / A+	A+ / A	A+ / A	A++ / A
Consumo eléctrico	Frio (W)	3150	3800	4700	5450
	Calor (W)	3500	3900	4450	5000
Corriente	Frio (A)	4.8	5.3	7.2	7.7
	Calor (A)	5.6	5.5	6.2	7.3
Alimentación	(V / f / Hz)	380 - 415 / 3 / 50	380 - 415 / 3 / 50	380 - 415 / 3 / 50	380 - 415 / 3 / 50
Rango de temperatura interior	Frio (°C)	+16 - +30	+16 - +30	+16 - +30	+16 - +30
	Calor (°C)	+16 - +30	+16 - +30	+16 - +30	+16 - +30
Rango de temperatura exterior	Frio (°C)	-20 - +48	-20 - +48	-20 - +48	-20 - +48
	Calor (°C)	-20 - +24	-20 - +24	-20 - +24	-20 - +24
Conexiones	Líquido (Pul.)	3/8	3/8	3/8	3/8
	Gas (Pul.)	5/8	5/8	5/8	5/8
Longitud precargada	(m)	5	5	7.5	7.5
Longitud máxima total (UI/UE)	(m)	65	75	75	75
Longitud vertical máxima	(m)	30	30	30	30
Cable de comunicación	(m)	2 × 0.75	2 × 0.75	2 × 0.75	2 × 0.75
UNIDAD INTERIOR					
Cable de alimentación	(n° × s)	3 × 1.5	3 × 1.5	3 × 1.5	3 × 1.5
Caudal de aire	(m³/h)	1800	2200	2400	2400
Presión estática	(Pa)	37	50	50	50
	(mín - máx)	0 - 100	0 - 150	0 - 150	0 - 200
Presión sonora	(dB(A))	40 - 44	38 - 41	38 - 41	38 - 41
Potencia sonora	(dB(A))	64	65	68	71
Deshumidificación	(L/h)	2.7	3	3.8	4.6
Unidad Ancho / alto / fondo	(mm)	1000 / 300 / 700	1400 / 300 / 700	1400 / 300 / 700	1400 / 300 / 700
Embalaje Ancho / alto / fondo	(mm)	1205 / 360 / 813	1601 / 365 / 813	1601 / 365 / 813	1678 / 365 / 808
Unidad Peso neto / bruto	(kg)	41 / 47	50 / 56	57 / 64	57 / 64
UNIDAD EXTERIOR					
Cable de alimentación	(n° × s)	5 × 2.5	5 × 2.5	5 × 2.5	5 × 2.5
Caudal de aire	(m³/h)	5900	5900	5900	6600
Presión sonora	(dB(A))	55	55	56	52
Potencia sonora	(dB(A))	70	71	71	72
Refrigerante		R32	R32	R32	R32
Carga de refrigerante	(kg)	2.5	2.65	2.8	3.6
Carga adicional	(g/m)	40	40	40	40
Unidad Ancho / alto / fondo	(mm)	940 / 820 / 460	940 / 820 / 460	940 / 820 / 460	900 / 1345 / 340
Embalaje Ancho / alto / fondo	(mm)	1073 / 868 / 563	1073 / 868 / 563	1073 / 868 / 563	1033 / 1395 / 443
Unidad Peso neto / bruto	(kg)	83 / 95	91 / 103	95 / 107	112 / 122

Descarga la aplicación **Gree+** escaneando este código QR:

