

TRIFÁSICO

MODELO		UM ST 36 3F	UM ST 42 3F	UM ST 48 3F	UM ST 60 3F
Código		3NGR3100	3NGR3105	3NGR3110	3NGR3115
Referencia UI		GUD100ZD/A-T	GUD125ZD/A-T	GUD140ZD/A-T	GUD160ZD/A-T
Referencia UE		GUD100W/NhA-X	GUD125W/NhA-X	GUD140W/NhA-X	GUD160W/NhA-X
Potencia	Frio (W)	10000 (3200 - 11500)	12100 (3600 - 12500)	13400 (6000 - 14500)	16000 (7400 - 16500)
	Calor (W)	12000 (2900 - 14500)	13500 (3900 - 15500)	15500 (5200 - 17000)	17000 (6200 - 18500)
Potencia -10°C	(W)	8060	9070	10410	11420
Eficiencia energética	SEER	6.1	5.6	5.6	5.1
	SCOP	4	4	4	4
Clase energética	Frio / Calor	A++ / A+	A+ / A	A+ / A	A++ / A
Consumo eléctrico	Frio (W)	3300	4050	4300	5400
	Calor (W)	3500	4000	4400	5400
Corriente	Frio (A)	5.1	5.9	6.6	7.7
	Calor (A)	5.6	6.1	6.7	7.6
Alimentación	(V / f / Hz)	380 - 415 / 3 / 50	380 - 415 / 3 / 50	380 - 415 / 3 / 50	380 - 415 / 3 / 50
Rango de temperatura interior	Frio (°C)	+16 - +30	+16 - +30	+16 - +30	+16 - +30
	Calor (°C)	+16 - +30	+16 - +30	+16 - +30	+16 - +30
Rango de temperatura exterior	Frio (°C)	-20 - +48	-20 - +48	-20 - +48	-20 - +48
	Calor (°C)	-20 - +24	-20 - +24	-20 - +24	-20 - +24
Conexiones	Líquido (Pul.)	3/8	3/8	3/8	3/8
	Gas (Pul.)	5/8	5/8	5/8	5/8
Longitud precargada	(m)	5	5	7.5	7.5
Longitud máxima total (UI/UE)	(m)	65	75	75	75
Longitud vertical máxima	(m)	30	30	30	30
Cable de comunicación	(m)	2 x 0.75	2 x 0.75	2 x 0.75	2 x 0.75
UNIDAD INTERIOR					
Cable de alimentación	(n° x s)	3 x 1.5	3 x 1.5	3 x 1.5	3 x 1.5
Caudal de aire	(m³/h)	1600	1800	2100	2300
Presión sonora	(dB(A))	43 - 47	42 - 47	44 - 50	45 - 53
Potencia sonora	(dB(A))	59	61	65	66
Unidad Ancho / alto / fondo	(mm)	1200 / 235 / 665	1570 / 235 / 665	1570 / 235 / 665	1570 / 235 / 665
Embalaje Ancho / alto / fondo	(mm)	1363 / 300 / 770	1729 / 300 / 770	1729 / 300 / 770	1729 / 300 / 770
Unidad Peso neto / bruto	(kg)	32 / 38	40 / 47	42 / 49	42 / 49
UNIDAD EXTERIOR					
Cable de alimentación	(n° x s)	5 x 2.5	5 x 2.5	5 x 2.5	5 x 2.5
Caudal de aire	(m³/h)	5900	5900	5900	6600
Presión sonora	(dB(A))	55	55	56	52
Potencia sonora	(dB(A))	70	71	71	72
Refrigerante		R32	R32	R32	R32
Carga de refrigerante	(kg)	2.5	2.65	2.8	3.6
Carga adicional	(g/m)	40	40	40	40
Unidad Ancho / alto / fondo	(mm)	940 / 820 / 460	940 / 820 / 460	940 / 820 / 460	900 / 1345 / 340
Embalaje Ancho / alto / fondo	(mm)	1073 / 868 / 563	1073 / 868 / 563	1073 / 868 / 563	1033 / 1395 / 443
Unidad Peso neto / bruto	(kg)	83 / 95	91 / 103	95 / 107	112 / 122

Descarga la aplicación **Green+** escaneando este código QR:

